Rockfon®

Part of the ROCKWOOL Group

Chicago Metallic™ T24 3810

Datasheet



Chicago Metallic™ T24 3810

- 24 mm grid with universal mainrunner and joggled-end cross tees
- 38mm main and cross tees for heavy load bearing and compatibility with accessories.
- A strong and stable grid which can be easily demounted
- Used to create concealed and exposed ceiling solutions
- Fire rating A1 as per EN 13501-1
- An audible ' click ' for fast and accurate installation

Cross-section



Compatible tiles

Concealed Semi-concealed Exposed

Coupling

Joggled end

Assortment

Product group		Component description	Height (mm)	Length (mm)	Body Material thickness	Colour	Pcs per pack	Lm per pack	Kg per pack
Main runner									
T24 MR CLICK		Main runner T24 Click	38	3600	0.4mm	02	20	72	29.3
Cross tee									
T24 CT CLICK		Cross tee T24 Click	38	1200	0.27mm	02	60	72	19.1
T24 CT CLICK			38	600	0.27mm	02	60	36	9.8
Wall angle options									
L24x24		L Wall angle 24 x 24mm	24	3000	0.4mm	02	40	120	19.7
W20x10x10x14		W Profile 20 x 10 x 10 x 14mm	20	3000	0.4mm	02	40	120	20
Accessories									
FH B		Hanger. Height 57.5mm. Max weight 35kg	57.5	21.5			200		3.21

Products in imperial units (foot and inch) are available upon request.

Position of slots and suspension holes

Product group	Component description	Height (mm)	Length (mm)	Slots	Distance between slots (mm)
T24 MR CLICK	Main runner T24 Click	38	3600	24	75 / 150 / 22 x 150 / 75
T24 CT CLICK	Cross tee T24 Click	38	1200	1	 600 / 600
T24 CT CLICK		38	600	0	 600

Performance

Load bearing capacity

Kg/m²	
	Maximum deflection
Hanger distance (mm)	3.3 mm
1200	21

Reaction to fire

Non-combustible

Environment

Fully Recyclable

Rockfon® is a registered trademark
of the ROCKWOOL Group.

07.2020 | All colour codes mentioned are based on the NCS - Natural Colour System® property of and used on license from NCS Colour AB, Stockholm 2012 or the RAL colour standard. Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.

Rockfon Singapore
ROCKWOOL Building Materials (Singapore) Pte Ltd.
No. 8, Tuas Avenue 2
Jurong Town
Singapore 639448
Tel: (+65) 6861 4722
Fax: (+65) 6862 3533

Rockfon Malaysia
Chicago Metallic (Malaysia) Sdn Bhd
PTD 220527,
Jalan Indah Gemilang,
Taman Perindustrian Cemerlang,
81800 Ulu Tiram,
Johor, Malaysia
Tel: (+607) 863 3539
Fax: (+607) 863 1525

Rockfon Hong Kong
ROCKWOOL Building Materials (Hong Kong) Ltd. Unit 301-2, 3/F, Koon Wah Building,
No.2 Yuen Shun Circuit,
Yuen Chau Kok, Shatin,
N.T., Hong Kong
Tel: (+852) 2576-6117
Mobile: (+852) 9161-7924

Rockfon®